

View Online at <https://aerobasegroup.com/nsn/5925-00-549-5825>

Body Style:

Rectangular dimensional envelope

Overall Length:

9.375 inches

Overall Height:

4.125 inches

Overall Width:

4.688 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.281 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations and 20.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

15000.0 ac all locations and 10000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Trip Delay Time In Seconds Per Rated Continuous Current:

360.000 at 125 pct all locations and 1050.000 at 125 pct all locations and 25.000 at 200 pct all locations and 55.000 at 200 pct all locations and 8.000 at 300 pct all locations and 11.000 at 300 pct all locations

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0