NSN 5925-00-549-7454

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-549-7454

Body Style: Rectangular dimensional envelope **Overall Length:** 3.625 inches **Overall Height:** 1.375 inches **Overall Width:** 2.328 inches **Case Material:** Metal **Unthreaded Mounting Hole Diameter:** 0.203 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 110.0 amperes ac all locations and 110.0 amperes dc all locations **Operating Voltage Type And Rating Per Pole In Volts:** 120.0 ac all locations and 28.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2000.0 ac all locations and 2000.0 dc all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 138.0 all locations **Reset Method:** Automatic **Internal Trip Release Configuration:** Series trip all locations **Trip Delay Time In Seconds Per Rated Continuous Current:** 10.000 at 200 pct all locations and 70.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Explosion proof and shockproof

Trip Release Ambient Tempurature Rating:

25.0 degrees celsius all locations

NSN 5925-00-549-7454

Circuit Breaker - Page 2 of 2



Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
9.000 ounces
Terminal Type And Quantity:
6 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A030a0