

View Online at <https://aerobasegroup.com/nsn/5925-00-552-4904>

**Overall Length:**

9.375 inches

**Overall Height:**

4.812 inches

**Overall Width:**

2.750 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Pole Quantity:**

2

**Arc Quenching Method:**

Deion

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac all locations and 20.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations and 250.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

15000.0 ac all locations and 10000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

122.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip w/separate reset

**Trip Release Duty Cycle:**

Continuous all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

90.000 at 125 pct all locations and 3600.000 at 125 pct all locations and 16.000 at 200 pct all locations and 45.000 at 200 pct all locations and 5.700 at 300 pct all locations and 13.000 at 300 pct all locations

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius all locations

**Special Features:**

Mtg holes spaced 7.250 in. C to c

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

4 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0