NSN 5925-00-552-5960

Circuit Breaker - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5925-00-552-5960

| Multipole-single actuator type |
|---|
| Body Length: |
| 5.000 inches |
| Body Width: |
| 4.750 inches |
| Case Material: |
| Plastic |
| Center To Center Distance Between Terminals Parallel To Length: |
| 3.625 inches |
| Center To Center Distance Between Terminals Parallel To Width: |
| 1.688 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.375 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 4.250 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.750 inches |
| Boss Height: |
| 0.312 inches |
| |
| Mounting Surface To Terminal End Distance: |
| Mounting Surface To Terminal End Distance: 4.625 inches |
| - |
| 4.625 inches |
| 4.625 inches Pole Quantity: |
| 4.625 inches Pole Quantity: 3 |
| 4.625 inches Pole Quantity: 3 Mounting Facility Type And Quantity: |
| 4.625 inches Pole Quantity: 3 Mounting Facility Type And Quantity: 6 unthreaded hole |
| 4.625 inches Pole Quantity: 3 Mounting Facility Type And Quantity: 6 unthreaded hole Storage Type: |
| 4.625 inches Pole Quantity: 3 Mounting Facility Type And Quantity: 6 unthreaded hole Storage Type: General purpose warehouse |
| 4.625 inches Pole Quantity: 3 Mounting Facility Type And Quantity: 6 unthreaded hole Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: |
| 4.625 inches Pole Quantity: 3 Mounting Facility Type And Quantity: 6 unthreaded hole Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 100.0 amperes ac all locations and 100.0 amperes dc all locations |
| 4.625 inches Pole Quantity: 3 Mounting Facility Type And Quantity: 6 unthreaded hole Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 100.0 amperes ac all locations and 100.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: |
| 4.625 inches Pole Quantity: 3 Mounting Facility Type And Quantity: 6 unthreaded hole Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 100.0 amperes ac all locations and 100.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 500.0 ac all locations and 250.0 dc all locations |
| 4.625 inches Pole Quantity: 3 Mounting Facility Type And Quantity: 6 unthreaded hole Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 100.0 amperes ac all locations and 100.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 500.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 4.625 inches Pole Quantity: 3 Mounting Facility Type And Quantity: 6 unthreaded hole Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 100.0 amperes ac all locations and 100.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 500.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations and 5000.0 dc all locations |
| 4.625 inches Pole Quantity: 3 Mounting Facility Type And Quantity: 6 unthreaded hole Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 100.0 amperes ac all locations and 100.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 500.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations and 5000.0 dc all locations Circuit Protection Type: |
| 4.625 inches Pole Quantity: 3 Mounting Facility Type And Quantity: 6 unthreaded hole Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 100.0 amperes ac all locations and 100.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 500.0 ac all locations and 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations and 5000.0 dc all locations Circuit Protection Type: Overcurrent all locations |

135.0 all locations

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

NSN 5925-00-552-5960

Circuit Breaker - Page 2 of 2



| Reset Method: |
|---|
| Manual |
| Main Contact Tripping Mechanism Type: |
| Trip free |
| Manual Actuator Type And Quantity: |
| 1 toggle |
| Actuator Function: |
| Trip-reset |
| Actuator Position Designation: |
| At pole two |
| Trip Delay Time In Seconds Per Rated Continuous Current: |
| 10.000 at 200 pct all locations and 110.000 at 200 pct all locations |
| nclosure Protection Type For Which Designed: |
| Fungus resistant |
| Trip Release Ambient Tempurature Rating: |
| 50.0 degrees celsius all locations |
| Special Features: |
| Shunt trip coil rated 32v and spst auxiliary switch connected in series w/shunt trip coil |
| Frequency In Hertz: |
| 60.0 all locations |
| Terminal Type And Quantity: |
| 6 compression |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| 4030a0 |
| |
| |
| |