## NSN 5925-00-553-2271

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-553-2271

**Body Style:** Multipole-single actuator type **Body Length:** 5.250 inches **Body Width:** 3.000 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 4.359 inches **Center To Center Distance Between Terminals Parallel To Width:** 1.000 inches **Unthreaded Mounting Hole Diameter:** 0.190 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: **4.359** inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.000 inches **Fragility Factor:** Moderately rugged **Boss Height:** 0.219 inches **Mounting Surface To Terminal End Distance:** 2.688 inches **Pole Quantity:** 1 **Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 4 threaded hole and 4 unthreaded hole Thready Qty Per Inch (tpi): **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac single location **Circuit Protection Type:** Overcurrent single location

**Trip Release Method:** 

Magnetic-hydraulic single location

## **NSN 5925-00-553-2271** Circuit Breaker - Page 2 of 2



Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.164 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
2.000 at 200 pct single location and 20.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Dustproof and fungus proof
Frequency In Hertz:
60.0 single location
Thread Series Designator:
Unc
Terminal Type And Quantity:
6 threaded stud
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A030a0