## NSN 5925-00-556-7530

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-556-7530 **Body Style:** Single pole type **Overall Length:** 2.172 inches **Body Width:** 0.750 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.562 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.812 inches **Mounting Surface To Terminal End Distance:** 1.344 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 2.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 30.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 400.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 120.0 single location **Reset Method:** Automatic **Internal Trip Release Configuration:** Series trip single location

**Thread Size:** 

0.138 inches

## NSN 5925-00-556-7530

Circuit Breaker - Page 2 of 2

No Fiig: A030a0



Trip Delay Time In Seconds Per Rated Continuous Current:
30.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Dustproof
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius single location
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: