

View Online at <https://aerobasegroup.com/nsn/5925-00-557-4030>

Overall Length:

6.000 inches

Overall Height:

3.968 inches

Overall Width:

2.750 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.188 inches

Pole Quantity:

2

Arc Quenching Method:

Deion

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac all locations and 30.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations and 125.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

7500.0 ac all locations and 7500.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Trip Delay Time In Seconds Per Rated Continuous Current:

100.000 at 200 pct all locations

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Special Features:

Mtg holes 2 rows of 2 holes each spaced 1.375 in. Apart, rows spaced 4.844 in. Apart off center

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0