## NSN 5925-00-557-4030

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-557-4030

view Online at https://defobasegroup.com/nsii/0320-00-007-4000
Overall Length:
6.000 inches
Overall Height:
3.968 inches
Overall Width:
2.750 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.188 inches
Pole Quantity:
2
Arc Quenching Method:
Deion
Mounting Facility Type And Quantity:
4 unthreaded hole
Maximum Continuous Load Current Rating Per Pole:
30.0 amperes ac all locations and 30.0 amperes dc all locations
Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac all locations and 125.0 dc all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
7500.0 ac all locations and 7500.0 dc all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations and time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Trip Delay Time In Seconds Per Rated Continuous Current:
100.000 at 200 pct all locations
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius all locations
Special Features:
Mtg holes 2 rows of 2 holes each append 1 275 in Apart rows append 1 244 in Apar

Mtg holes 2 rows of 2 holes each spaced 1.375 in.Apart, rows spaced 4.844 in. Apart off center

## NSN 5925-00-557-4030

Circuit Breaker - Page 2 of 2



Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A030a0