## NSN 5925-00-561-7328

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-561-7328

**Body Style:** 

Multipole-multiple actuator type

**Body Length:** 

2.187 inches

**Body Width:** 

2.594 inches

**Case Material:** 

**Plastic** 

**Center To Center Distance Between Terminals Parallel To Length:** 

1.437 inches

**Center To Center Distance Between Terminals Parallel To Width:** 

0.875 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.812 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.875 inches

**Fragility Factor:** 

Moderately rugged

**Mounting Surface To Terminal End Distance:** 

2.234 inches

**Pole Quantity:** 

Air

**Arc Quenching Method:** 

**Mounting Facility Type And Quantity:** 

6 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

**Maximum Continuous Load Current Rating Per Pole:** 

100.0 amperes ac all locations and 100.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:** 

120.0 ac all locations and 30.000 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

3500.0 ac all locations and 6000.0 dc all locations

**Circuit Protection Type:** 

Overcurrent all locations

**Trip Release Method:** 

Magnetic all locations

**Trip Release Characteristic:** 

Time delay all locations

## **NSN 5925-00-561-7328** Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
138.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
3 push-pull
Actuator Function:
Reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One, two, and three linked
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
15.000 at 200 pct all locations and 65.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
General purpose
Frequency In Hertz:
400.0 all locations
Thread Series Designator:
Unc
Terminal Type And Quantity:
6 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A030a0