# NSN 5925-00-570-4643

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-570-4643

#### **Body Style:**

Multipole-single actuator type

#### **Body Length:**

2.000 inches

## Body Width:

2.170 inches

#### **Body Height:**

1.545 inches

#### **Case Material:**

Plastic

#### Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

#### **Boss Height:**

0.125 inches

#### **Pole Quantity:**

3

### Mounting Facility Type And Quantity:

1 clip

#### Maximum Continuous Load Current Rating Per Pole:

2.5 amperes ac all locations

#### **Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac all locations

### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

#### Trip Release Method:

Magnetic-hydraulic all locations

#### **Trip Release Characteristic:**

Time delay all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

#### **Reset Method:**

Manual

#### Main Contact Tripping Mechanism Type:

Trip free

### Manual Actuator Type And Quantity:

1 toggle

## **Actuator Function:**

Trip-reset

### Actuator Position Designation:

At pole two

# NSN 5925-00-570-4643

Circuit Breaker - Page 2 of 2



## Internal Trip Release Configuration:

Series trip all locations

#### Trip Delay Time In Seconds Per Rated Continuous Current:

3.000 at 200 pct all locations and 20.000 at 200 pct all locations

Frequency In Hertz:

400.0 all locations

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0