NSN 5925-00-570-4643



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-570-4643 **Body Style:** Multipole-single actuator type **Body Length:** 2.000 inches **Body Width:** 2.170 inches **Body Height:** 1.545 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 0.625 inches **Boss Height:** 0.125 inches **Pole Quantity: Mounting Facility Type And Quantity:** 1 clip **Maximum Continuous Load Current Rating Per Pole:** 2.5 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 ac all locations **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 1000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic-hydraulic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset

At pole two

Actuator Position Designation:

NSN 5925-00-570-4643

Circuit Breaker - Page 2 of 2



Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

3.000 at 200 pct all locations and 20.000 at 200 pct all locations

Frequency In Hertz:

400.0 all locations

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0