NSN 5925-00-574-2522

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-574-2522

Body Style:

Multipole-single actuator type

Body Length:

10.125 inches

Body Width:

8.250 inches

Body Height:

4.062 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

9.125 inches

Center To Center Distance Between Terminals Parallel To Width:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.312 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

7.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.750 inches

Boss Height:

0.250 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

300.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

25000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 all locations

Reset Method:

Automatic

NSN 5925-00-574-2522

Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity: 1 toggle Actuator Function: Trip-reset Actuator Position Designation:

At pole two

Trip Release Ambient Tempurature Rating:

40.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A030a0