

View Online at <https://aerobasegroup.com/nsn/5925-00-581-3930>

Body Style:

Multipole-single actuator type

Body Length:

5.250 inches

Body Width:

2.984 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

4.359 inches

Center To Center Distance Between Terminals Parallel To Width:

0.980 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.359 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.000 inches

Boss Height:

0.219 inches

Mounting Surface To Terminal End Distance:

3.969 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Ultimate Trip Time Per Pole In Seconds:

600.000 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.190 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

100.000 at 200 pct all locations

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unf

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0