NSN 5925-00-581-4932

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-581-4932 **Overall Length: 3.156** inches **Overall Height:** 1.906 inches **Overall Width:** 1.875 inches **Case Material:** Plastic Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.406 inches **Pole Quantity: Arc Quenching Method:** Air **Mounting Facility Type And Quantity:** 2 threaded hole Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 105.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 4800.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 138.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 push-pull **Actuator Function:** Reset

Thread Size:

0.190 inches

NSN 5925-00-581-4932

Circuit Breaker - Page 2 of 2



Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct single location and 60.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Dustproof

Trip Release Ambient Tempurature Rating:

25.0 degrees celsius single location

Precious Material:

Silver

Thread Series Designator:

Unf

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0