NSN 5925-00-583-2617



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-583-2617 **Body Style:** Multipole-multiple actuator type **Bushing Length:** 0.250 inches **Body Length:** 2.189 inches **Body Width:** 2.250 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 1.094 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.750 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 2.000 inches **Pole Quantity: Arc Quenching Method:** Air **Mounting Facility Type And Quantity:** 3 threaded bushing w/panel seal Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 10.0 amperes ac all locations and 10.0 amperes dc all locations Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac all locations and 30.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac all locations and 6000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

120.0 all locations

NSN 5925-00-583-2617 Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
3 push-pull
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One, two, and three linked
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.469 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
5.000 at 200 pct all locations and 15.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Shock resistant and vibration resistant
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius all locations
Frequency In Hertz:
400.0 all locations
Thread Series Designator:
Uns
Terminal Type And Quantity:
6 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0