NSN 5925-00-583-8119



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-583-8119 **Body Style:** Single pole type **Body Length:** 1.812 inches **Body Width:** 1.188 inches **Body Height:** 1.875 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 0.625 inches **Unthreaded Mounting Hole Diameter:** 0.174 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.574 inches **Pole Quantity: Arc Quenching Method:** Air **Mounting Facility Type And Quantity:** 2 unthreaded hole **Maximum Continuous Load Current Rating Per Pole:**

15.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

30.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

900.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

NSN 5925-00-583-8119 Circuit Breaker - Page 2 of 2



Actuator Function:
Reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Trip Delay Time In Seconds Per Rated Continuous Current:
3.000 at 200 pct single location
Special Features:
Terminals enclosed in two female sockets
Terminal Type And Quantity:
2 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0