

View Online at <https://aerobasegroup.com/nsn/5925-00-601-6344>

Body Style:

Single pole type

Body Length:

2.844 inches

Body Width:

0.969 inches

Body Height:

2.359 inches

Case Material:

Plastic

Boss Height:

0.187 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 terminal

Storage Type:

General purpose warehouse

Features Provided:

Ground fault protection

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Instantaneous single location and time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

15.000 at 200 pct single location and 110.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant

Trip Release Ambient Temperature Rating:

50.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

1 compression and 1 clip

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0