## NSN 5925-00-603-8077



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-603-8077 **Body Style:** Single pole type **Body Length:** 3.750 inches **Body Width:** 1.000 inches **Body Height:** 2.344 inches **Case Material: Plastic Boss Height:** 0.156 inches **Pole Quantity: Mounting Facility Type And Quantity:** 6 terminal **Maximum Continuous Load Current Rating Per Pole:** 50.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal-magnetic single location **Trip Release Characteristic:** Instantaneous single location and time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** 

Trip-reset

**Actuator Position Designation:** 

At each pole

**Trip Delay Time In Seconds Per Rated Continuous Current:** 

240.000 at 200 pct single location

## NSN 5925-00-603-8077

Circuit Breaker - Page 2 of 2



nciosure Protection	Type For	wnicn	Designea
ungus resistant			

**Trip Release Ambient Tempurature Rating:** 

40.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

**Terminal Type And Quantity:** 

1 compression and 1 clip

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A030a0