

View Online at <https://aerobasegroup.com/nsn/5925-00-615-1769>

Case Material:

Plastic

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

50.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

400.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

200.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Actuator Function:

Trip-reset

Thread Size:

0.164 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

36.000 at 125 pct all locations and 10.000 at 200 pct all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0