## NSN 5925-00-615-7071

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-615-7071 **Body Style:** Single pole type **Overall Length:** 50.8 millimeters **Body Width:** 19.81 millimeters **Case Material:** Metal **Center To Center Distance Between Terminals Parallel To Length:** Between 17.14 millimeters and 17.27 millimeters **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 39.62 millimeters **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 34.97 millimeters **Pole Quantity: Arc Quenching Method:** Deion **Mounting Facility Type And Quantity:** 2 terminal Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 12.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Instantaneous single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** 

Automatic

**Internal Trip Release Configuration:** 

Series trip single location

## NSN 5925-00-615-7071

Circuit Breaker - Page 2 of 2



Inclosure Protection Type For Which Designed:
Hermetically sealed
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius single location
Terminal Type And Quantity:
2 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A030a0