

View Online at <https://aerobasegroup.com/nsn/5925-00-617-2018>

Body Style:

Single pole type

Body Length:

Between 2.436 inches and 2.564 inches

Body Width:

Between 0.686 inches and 0.814 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 1.875 inches and 1.999 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.998 inches and 2.126 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.061 inches and 0.189 inches

Mounting Surface To Terminal End Distance:

2.505 inches

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

115.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1500.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

3.000 at 200 pct single location and 9.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant and explosion resistant

Frequency In Hertz:

400.0 single location

Precious Material And Location:

Terminal and contact surfaces silver

Precious Material:

Silver

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0