

View Online at <https://aerobasegroup.com/nsn/5925-00-620-3968>

Body Style:

Multipole-single actuator type

Body Length:

4.125 inches

Body Width:

3.344 inches

Body Height:

3.375 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

2.625 inches

Center To Center Distance Between Terminals Parallel To Width:

1.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.937 inches

Boss Height:

0.125 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

2 threaded stud

Thread Qty Per Inch (tpi):

24

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations and 15.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

125.0 ac all locations and 125.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations and 5000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 all locations

Ultimate Trip Time Per Pole In Seconds:

3600.000 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

External Actuator Linkage Arrangement:

One, two, and three linked

Thread Size:

0.216 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct all locations and 100.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Shockproof and vibrationproof

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Special Features:

Instantaneous trip settings 600 amp ac and 800 amp dc

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0