

View Online at <https://aerobasegroup.com/nsn/5925-00-620-5861>

Body Style:

Multipole-single actuator type

Body Length:

5.000 inches

Body Width:

4.750 inches

Body Height:

4.625 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

3.625 inches

Center To Center Distance Between Terminals Parallel To Width:

1.688 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

Boss Height:

0.312 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

2 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

175.0 amperes ac all locations and 175.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

125.0 ac all locations and 125.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations and 5000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct all locations and 210.000 at 200 pct all locations

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Specification Or Standard:

Alb type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0