

View Online at <https://aerobasegroup.com/nsn/5925-00-620-5861>

**Body Style:**

Multipole-single actuator type

**Body Length:**

5.000 inches

**Body Width:**

4.750 inches

**Body Height:**

4.625 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

3.625 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.688 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

4.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.500 inches

**Boss Height:**

0.312 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

175.0 amperes ac all locations and 175.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

125.0 ac all locations and 125.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

10000.0 ac all locations and 5000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

115.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**Trip Delay Time In Seconds Per Rated Continuous Current:**

10.000 at 200 pct all locations and 210.000 at 200 pct all locations

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius all locations

**Frequency In Hertz:**

60.0 all locations

**Specification Or Standard:**

Alb type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0