NSN 5925-00-622-0342

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-622-0342
Overall Length:
Between 4.636 inches and 4.700 inches
Overall Height:
Between 1.168 inches and 1.232 inches
Overall Width:
Between 1.968 inches and 2.032 inches
Case Material:
Plastic
Switch Contact Arrangement:
Single pole, double throw
Fragility Factor:
Moderately rugged
Pole Quantity:
1
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
2 clip
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
5.0 amperes ac single location
Operating Voltage Type And Rating Per Pole In Volts:
250.0 ac single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1000.0 ac single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Magnetic-hydraulic single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:

Trip-reset

NSN 5925-00-622-0342 Circuit Breaker - Page 2 of 2



Actuator Position Designation:
At pole one
Auxiliary Switch Function And Quantity:
1 alarm
Internal Trip Release Configuration:
Series trip single location
Switch Location And Position Designation:
Internal at pole one
Trip Delay Time In Seconds Per Rated Continuous Current:
0.150 at 200 pct single location and 1.500 at 200 pct single location
Inclosure Protection Type For Which Designed:
Fungus resistant
Switch Terminal Type:
Tab, solder lug
Switch Current Rating And Type In Amps:
10.0 ac
Switch Voltage Rating And Type In Volts:
250.0 ac
Frequency In Hertz:
60.0 single location
Unpackaged Unit Weight:
2.500 ounces
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0