NSN 5925-00-624-3052

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-624-3052

# Body Style:

Rectangular dimensional envelope

**Overall Length:** 

8.438 inches

## **Overall Height:**

3.875 inches

**Overall Width:** 

5.625 inches

#### **Unthreaded Mounting Hole Diameter:**

Between 0.203 inches and 0.438 inches

### Pole Quantity:

3

#### Mounting Facility Type And Quantity:

5 unthreaded hole

#### Features Provided:

Adjustable trip release

#### Maximum Continuous Load Current Rating Per Pole:

125.0 amperes ac all locations

#### **Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations

#### Circuit Protection Type:

Overcurrent all locations

#### **Trip Release Method:**

Thermal-magnetic all locations

#### **Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

105.0 all locations

#### Adjustable Trip Setting Current Range Per Pole In Amps:

+650.0/+1300.0 ac all locations

#### Trip Delay Time In Seconds Per Rated Continuous Current:

25.000 at 600 pct all locations

#### Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

#### Frequency In Hertz:

60.0 all locations

#### **Terminal Type And Quantity:**

6 screw

Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 5925-00-624-3052

Circuit Breaker Tripper - Page 2 of 2

Demilitarization:

No

Fiig:

A030a0

