

View Online at <https://aerobasegroup.com/nsn/5925-00-626-4191>

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

75.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

440.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

15000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

115.0 all locations

**Reset Method:**

Automatic

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Reset

**Actuator Position Designation:**

At pole three

**Internal Trip Release Configuration:**

Shunt trip all locations

**Inclosure Protection Type For Which Designed:**

Dustproof

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius all locations

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0