NSN 5925-00-628-7762

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-628-7762

## **Body Style:**

Rectangular dimensional envelope

**Overall Length:** 

8.438 inches

# **Overall Height:**

4.000 inches

## **Overall Width:**

6.938 inches

#### **Unthreaded Mounting Hole Diameter:**

0.344 inches

#### **Pole Quantity:**

3

### Mounting Facility Type And Quantity:

4 unthreaded hole

#### Features Provided:

Adjustable trip release

## Maximum Continuous Load Current Rating Per Pole:

400.0 amperes ac all locations

## **Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations

# Circuit Protection Type:

Overcurrent all locations

#### **Trip Release Method:**

Thermal-magnetic all locations

## **Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

## Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

105.0 all locations

## Adjustable Trip Setting Current Range Per Pole In Amps:

+990.0/+1010.0 ac all locations

## Trip Delay Time In Seconds Per Rated Continuous Current:

25.000 at 600 pct all locations

## Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

#### Frequency In Hertz:

60.0 all locations

## **Terminal Type And Quantity:**

6 screw

Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 5925-00-628-7762

Circuit Breaker Tripper - Page 2 of 2

Demilitarization:

No

Fiig:

A030a0

