NSN 5925-00-628-7774

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-628-7774 **Body Style:** Rectangular dimensional envelope **Overall Length:** 8.438 inches **Overall Height:** 3.875 inches **Overall Width:** 4.500 inches **Unthreaded Mounting Hole Diameter:** Between 0.406 inches and 0.531 inches **Pole Quantity:** 3 **Mounting Facility Type And Quantity:** 6 unthreaded hole Storage Type: General purpose warehouse **Features Provided:** Adjustable trip release **Maximum Continuous Load Current Rating Per Pole:** 250.0 amperes ac all locations and 250.0 amperes dc all locations **Operating Voltage Type And Rating Per Pole In Volts:** 500.0 ac all locations and 250.0 dc all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 105.0 all locations **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole two Adjustable Trip Setting Current Range Per Pole In Amps: +880.0/+1530.0 ac all locations and +1150.0/+1765.0 dc all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

25.000 at 600 pct all locations

Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

NSN 5925-00-628-7774

Circuit Breaker Tripper - Page 2 of 2



60.0 all locations

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0