

View Online at <https://aerobasegroup.com/nsn/5925-00-628-7778>

Body Style:

Rectangular dimensional envelope

Overall Length:

8.438 inches

Overall Height:

3.875 inches

Overall Width:

4.500 inches

Unthreaded Mounting Hole Diameter:

Between 0.406 inches and 0.531 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 unthreaded hole

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

350.0 amperes ac all locations and 350.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations and 250.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

105.0 all locations

Adjustable Trip Setting Current Range Per Pole In Amps:

+1380.0/+2280.0 ac all locations and +1600.0/+2285.0 dc all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

25.000 at 600 pct all locations

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0