NSN 5925-00-642-1114



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-642-1114 **Overall Length:** 4.250 inches **Overall Height:** 3.906 inches **Overall Width:** 3.000 inches **Case Material: Plastic** Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 4.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.969 inches **Pole Quantity: Arc Quenching Method: Mounting Facility Type And Quantity:** 2 threaded stud **Maximum Continuous Load Current Rating Per Pole:** 50.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 130.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle

Actuator Function:

Reset

Trip Delay Time In Seconds Per Rated Continuous Current:

240.000 at 150 pct all locations

NSN 5925-00-642-1114

Circuit Breaker - Page 2 of 2



Trip Release Ambient Tempurature Rating:
25.0 degrees celsius all locations
Precious Material:
Silver
Terminal Type And Quantity:
6 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A030a0