NSN 5925-00-647-3469

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-647-3469

Overall Length:					
9.375 inches					
Overall Height:					
4.812 inches					
Overall Width:					
4.125 inches					
Case Material:					
Plastic					
Pole Quantity:					
3					
Arc Quenching Method:					
Deion					
Mounting Facility Type And Quantity:					
4 unthreaded hole					
Maximum Continuous Load Current Rating Per Pole:					
70.0 amperes ac all locations					
Operating Voltage Type And Rating Per Pole In Volts:					
15000.0 ac all locations and 15000.0 dc all locations					
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:					
15000.0 ac all locations and 15000.0 dc all locations					
Circuit Protection Type:					
Overcurrent all locations					
Trip Release Method:					
Thermal-magnetic all locations					
Trip Release Characteristic:					
Instantaneous all locations and time delay all locations					
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:					
125.0 all locations					
Reset Method:					
Manual					
Main Contact Tripping Mechanism Type:					
Trip free					
Manual Actuator Type And Quantity:					
1 toggle					
Actuator Function:					
Trip w/separate reset					
Trip Release Duty Cycle:					
Continuous all locations					
Trip Delay Time In Seconds Per Rated Continuous Current:					
7200.000 at 125 pct all locations and 220.000 at 200 pct all locations and 45.000 at 300 pct all locations					
Trip Release Ambient Tempurature Rating:					
25.0 degrees celsius all locations					

NSN 5925-00-647-3469

Circuit Breaker - Page 2 of 2



S	ne	cial	Feature	es:
J	μυ	viai	. catar	5 .

8 plug-in terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0