# NSN 5925-00-655-1158

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-655-1158

## Body Style:

Rectangular dimensional envelope

**Overall Length:** 

10.156 inches

## **Overall Height:**

4.750 inches

#### **Overall Width:**

4.750 inches

#### **Unthreaded Mounting Hole Diameter:**

0.250 inches

**Fragility Factor:** 

Moderately rugged

#### **Pole Quantity:**

3

#### Mounting Facility Type And Quantity:

4 unthreaded hole

#### Storage Type:

General purpose warehouse

#### Features Provided:

Adjustable trip release

#### Maximum Continuous Load Current Rating Per Pole:

25.0 amperes ac all locations

#### **Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

#### **Trip Release Method:**

Thermal-magnetic all locations

#### Trip Release Characteristic:

Instantaneous all locations

# Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

# Manual Actuator Type And Quantity:

1 toggle

# Actuator Function:

Trip-reset

# Actuator Position Designation:

At pole two

# Adjustable Trip Setting Current Range Per Pole In Amps:

+300.0/+350.0 ac all locations

## Trip Release Ambient Tempurature Rating:

50.0 degrees celsius all locations

# NSN 5925-00-655-1158

Circuit Breaker Tripper - Page 2 of 2

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A030a0

