## NSN 5925-00-655-1166

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-655-1166

view Online at https://aerobasegroup.com/hsn/5925-00-655-1166
Body Style:
Rectangular dimensional envelope
Overall Length:
7.500 inches
Overall Height:
3.781 inches
Overall Width:
3.938 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
4 unthreaded hole
Storage Type:
General purpose warehouse
Features Provided:
Adjustable trip release
Maximum Continuous Load Current Rating Per Pole:
125.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
500.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations and time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
140.0 all locations
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Adjustable Trip Setting Current Range Per Pole In Amps:
+1500.0/+3000.0 ac all locations
Trip Delay Time In Seconds Per Rated Continuous Current:

**Trip Release Ambient Tempurature Rating:** 

20.000 at 600 pct all locations and 32.000 at 600 pct all locations

50.0 degrees celsius all locations

## NSN 5925-00-655-1166

Circuit Breaker Tripper - Page 2 of 2



Frequency	In	Hertz:

60.0 all locations

**Unpackaged Unit Weight:** 

3.100 pounds

**Terminal Type And Quantity:** 

6 compression

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A030a0