NSN 5925-00-655-1167

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-655-1167

Body Style:

Rectangular dimensional envelope

Overall Length:

7.500 inches

Overall Height:

3.781 inches

Overall Width:

3.938 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

150.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Adjustable Trip Setting Current Range Per Pole In Amps:

+600.0/+1300.0 ac all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

270.000 at 200 pct all locations and 480.000 at 200 pct all locations

NSN 5925-00-655-1167

Circuit Breaker Tripper - Page 2 of 2



Trip Release Ambient Tempurature Rating: 50.0 degrees celsius all locations Frequency In Hertz: 60.0 all locations Unpackaged Unit Weight: 3.100 pounds Terminal Type And Quantity: 6 compression Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A030a0