NSN 5925-00-655-1172

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-655-1172

view Orinine at https://derobasegroup.com/nsi//0920-000-1172
Body Style:
Rectangular dimensional envelope
Overall Length:
7.500 inches
Overall Height:
3.781 inches
Overall Width:
3.937 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
4 unthreaded hole
Storage Type:
General purpose warehouse
Features Provided:
Adjustable trip release
Maximum Continuous Load Current Rating Per Pole:
225.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
500.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations and time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
140.0 all locations
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Adjustable Trip Setting Current Range Per Pole In Amps:
+1500.0/+3000.0 ac all locations
Trip Delay Time In Seconds Per Rated Continuous Current:

Trip Release Ambient Tempurature Rating:

20.000 at 600 pct all locations and 32.000 at 600 pct all locations

50.0 degrees celsius all locations

NSN 5925-00-655-1172

Circuit Breaker Tripper - Page 2 of 2



Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
3.100 pounds
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A030a0