## NSN 5925-00-655-1174

Circuit Breaker Tripper - Page 1 of 2



View Online at https://aerobasegroup.com/psp/5025-00-655-1174

| View Online at https://aerobasegroup.com/nsn/5925-00-655-1174          |
|--|
| Body Style:  |
| Rectangular dimensional envelope                                       |
| Overall Length:  |
| 7.500 inches   |
| Overall Height:  |
| 3.938 inches   |
| Overall Width:   |
| 8.000 inches   |
| Unthreaded Mounting Hole Diameter:                                     |
| 0.250 inches   |
| Pole Quantity:   |
| 3  |
| Mounting Facility Type And Quantity:                                   |
| 4 unthreaded hole  |
| Storage Type:  |
| General purpose warehouse  |
| Features Provided:   |
| Adjustable trip release  |
| Maximum Continuous Load Current Rating Per Pole:                       |
| 250.0 amperes ac all locations   |
| Operating Voltage Type And Rating Per Pole In Volts:                   |
| 500.0 ac all locations   |
| Circuit Protection Type:   |
| Overcurrent all locations  |
| Trip Release Method:   |
| Thermal-magnetic all locations   |
| Trip Release Characteristic:   |
| Instantaneous all locations and time delay all locations               |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 140.0 all locations  |
| Manual Actuator Type And Quantity:                                     |
| 1 toggle   |
| Actuator Function:   |
| Trip-reset   |
| Actuator Position Designation:   |
| At pole two  |
| Adjustable Trip Setting Current Range Per Pole In Amps:                |
| +650.0/+1300.0 ac all locations  |
| Trip Dolay Time In Seconds Per Pated Continuous Current:               |

Trip Delay Time In Seconds Per Rated Continuous Current:

20.000 at 600 pct all locations and 32.000 at 600 pct all locations

**Trip Release Ambient Tempurature Rating:** 

50.0 degrees celsius all locations

## NSN 5925-00-655-1174

Circuit Breaker Tripper - Page 2 of 2



| Frequency     | In  | не | rtz |
|---------------|-----|----|-----|
| 60.0 all loca | tio | ns |     |

**Unpackaged Unit Weight:** 

3.100 pounds

**Terminal Type And Quantity:** 

6 compression

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A030a0