

View Online at <https://aerobasegroup.com/nsn/5925-00-660-3699>

Case Material:

Metal

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 threaded stud

Maximum Continuous Load Current Rating Per Pole:

400.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

25000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Reset Method:

Automatic

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

0.050 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 eyelet

Reference Number Differentiating Characteristics:

As differentiated in poles continuous load rating overload protection environmental protection over-all dimensions and mounting data

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0