NSN 5925-00-660-3813

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-660-3813

#### Body Style:

Multipole-single actuator type

## Body Length:

6.000 inches

## Body Width:

3.000 inches

#### **Body Height:**

3.594 inches

## Case Material:

Plastic

## Center To Center Distance Between Terminals Parallel To Length:

## 4.594 inches

Center To Center Distance Between Terminals Parallel To Width:

#### 1.500 inches

Unthreaded Mounting Hole Diameter:

## 0.190 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.594 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

#### Boss Height:

0.219 inches

#### Pole Quantity:

2

## Mounting Facility Type And Quantity:

4 unthreaded hole

## Storage Type:

General purpose warehouse

## Maximum Continuous Load Current Rating Per Pole:

100.0 amperes ac all locations and 100.0 amperes dc all locations

## Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations and 250.0 dc all locations

## Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

20000.0 ac all locations

## **Circuit Protection Type:**

Overcurrent all locations

## Trip Release Method:

Thermal-magnetic all locations

## Trip Release Characteristic:

Instantaneous all locations and time delay all locations

## Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

105.0 all locations

# **NSN 5925-00-660-3813** Circuit Breaker - Page 2 of 2



M	lanual
М	ain Contact Tripping Mechanism Type:
Τı	rip free
М	anual Actuator Type And Quantity:
1	toggle
A	ctuator Function:
Τı	rip-reset
A	ctuator Position Designation:
A	t pole one
Tı	rip Delay Time In Seconds Per Rated Continuous Current:
22	2.000 at 200 pct all locations and 30.000 at 200 pct all locations
In	closure Protection Type For Which Designed:
G	eneral purpose
Tı	rip Release Ambient Tempurature Rating:
4(	0.0 degrees celsius all locations
F	requency In Hertz:
60	0.0 all locations
Т	erminal Type And Quantity:
4	compression
S	helf Life:
N	/a
U	nit Of Measure:
D	emilitarization:
N	0
Fi	iig:
A	030a0