NSN 5925-00-660-3892

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-660-3892

Body Style: Multipole-multiple actuator type **Body Length:** 3.790 inches **Body Width:** 3.060 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** Between 3.050 inches and 3.070 inches **Center To Center Distance Between Terminals Parallel To Width:** Between 2.040 inches and 2.080 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** Between 2.740 inches and 2.760 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.060 inches **Boss Height:** Between 0.145 inches and 0.175 inches **Mounting Surface To Terminal End Distance:** 3.310 inches **Pole Quantity:** 3 **Mounting Facility Type And Quantity:** 6 threaded hole Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 40.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 416.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1500.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations

150.0 all locations

Ultimate Trip Time Per Pole In Seconds:

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

70.000 all locations

NSN 5925-00-660-3892 Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
3 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One, two, and three linked
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
8.000 at 400 pct all locations
Inclosure Protection Type For Which Designed:
Dustproof
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius all locations
Frequency In Hertz:
400.0 all locations
Thread Series Designator:
Unc
Terminal Type And Quantity:
6 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:
A030a0