## NSN 5925-00-660-6369

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-660-6369

**Body Style:** Multipole-multiple actuator type **Body Length:** 3.719 inches **Body Width:** 3.052 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 3.063 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.990 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.990 inches **Boss Height:** 0.156 inches **Mounting Surface To Terminal End Distance:** 3.239 inches **Pole Quantity:** 3 **Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 6 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 3.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 416.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1500.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic-hydraulic all locations **Trip Release Characteristic:** 

Time delay all locations

## **NSN 5925-00-660-6369** Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
150.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
3 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One, two, and three linked
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
25.000 at 200 pct all locations and 90.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Frequency In Hertz:
400.0 all locations
Unpackaged Unit Weight:
1.770 pounds
Thread Series Designator:
Unc
Terminal Type And Quantity:
6 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0