

View Online at <https://aerobasegroup.com/nsn/5925-00-665-7706>

Case Material:

Plastic

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 slot

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Instantaneous single location and time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Automatic

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

1.600 at 125 pct single location and 7.000 at 125 pct single location and 0.320 at 200 pct single location and 0.980 at 200 pct single location and 0.140 at 300 pct single location and 0.400 at 300 pct single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0