

View Online at <https://aerobasegroup.com/nsn/5925-00-666-4696>

Body Style:

Multipole-single actuator type

Body Length:

17.500 inches

Body Width:

9.000 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Width:

6.000 inches

Unthreaded Mounting Hole Diameter:

0.438 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

22.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.750 inches

Mounting Surface To Terminal End Distance:

13.187 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

600.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

20000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Relay trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

60.000 18 stage minor all locations

Trip Release Ambient Temperature Rating:

50.0 degrees celsius all locations

Test Data Document:

81349-mil-c-17361 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0