## NSN 5925-00-681-4677

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-681-4677

**Thread Pitch Diameters:** 

+0.3503/+0.3537 inches

**Body Style:** 

Single pole type

**Bushing Length:** 

Between 0.360 inches and 0.380 inches

**Body Length:** 

Between 1.448 inches and 1.510 inches

**Body Width:** 

Between 0.567 inches and 0.629 inches

**Case Material:** 

Metal

Center To Center Distance Between Terminals Parallel To Length:

Between 0.870 inches and 0.880 inches

**Fragility Factor:** 

Moderately rugged

**Mounting Surface To Terminal End Distance:** 

Between 1.524 inches and 1.586 inches

**Pole Quantity:** 

.

**Arc Quenching Method:** 

Magnetic blowout

**Mounting Facility Type And Quantity:** 

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

**Maximum Continuous Load Current Rating Per Pole:** 

1.5 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:** 

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

300.0 ac all locations

**Circuit Protection Type:** 

Overcurrent all locations

**Trip Release Method:** 

Magnetic-hydraulic all locations

**Trip Release Characteristic:** 

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 

115.0 all locations

## **NSN 5925-00-681-4677** Circuit Breaker - Page 2 of 2

