## NSN 5925-00-683-2884

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-683-2884 **Body Style:** Single pole type **Bushing Length:** 0.250 inches **Body Length:** 2.188 inches **Body Width:** 0.750 inches **Case Material:** Ceramic **Center To Center Distance Between Terminals Parallel To Length:** 0.906 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 1.812 inches **Mounting Surface To Terminal End Distance:** 1.312 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 threaded hole Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac single location and 30.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location and 4000.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic-hydraulic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 115.0 single location **Reset Method:** Manual

Trip free

**Main Contact Tripping Mechanism Type:** 

## **NSN 5925-00-683-2884** Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 push-pull
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
10.000 at 200 pct single location and 60.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Dustproof and explosion proof
Frequency In Hertz:
400.0 single location
Unpackaged Unit Weight:
1.500 ounces
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0