NSN 5925-00-686-2769

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-686-2769

Body Length:
10.000 inches
Body Width:
4.500 inches
Body Height:
3.938 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
8.675 inches
Center To Center Distance Between Terminals Parallel To Width:
1.500 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
8.675 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.500 inches
Boss Height:
0.250 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
4 unthreaded hole
4 unthreaded hole Storage Type:
Storage Type:
Storage Type: General purpose warehouse
Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole:
Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 100.0 amperes ac all locations
Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 100.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts:
Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 100.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations
Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 100.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 100.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 15000.0 ac all locations
Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 100.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 15000.0 ac all locations Circuit Protection Type:
Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 100.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 15000.0 ac all locations Circuit Protection Type: Overcurrent all locations
Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 100.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 15000.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method:
Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 100.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 15000.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Thermal-magnetic all locations Trip Release Characteristic: Instantaneous all locations
Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 100.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 15000.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Thermal-magnetic all locations Trip Release Characteristic: Instantaneous all locations Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 100.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 600.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 15000.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Thermal-magnetic all locations Trip Release Characteristic: Instantaneous all locations

Manual

NSN 5925-00-686-2769 Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0