

View Online at <https://aerobasegroup.com/nsn/5925-00-686-3327>

**Overall Length:**

2.578 inches

**Overall Height:**

2.188 inches

**Overall Width:**

0.750 inches

**Case Material:**

Plastic

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.813 inches

**Pole Quantity:**

1

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

2 threaded stud

**Maximum Continuous Load Current Rating Per Pole:**

60.0 amperes ac single location and 60.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac single location and 30.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

3500.0 ac single location and 6000.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

115.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push-pull

**Actuator Function:**

Reset

**Trip Delay Time In Seconds Per Rated Continuous Current:**

15.000 at 200 pct single location and 55.000 at 200 pct single location and 2.000 at 400 pct single location and 7.000 at 400 pct single location

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius single location

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0