

View Online at <https://aerobasegroup.com/nsn/5925-00-686-3364>

Overall Length:

2.530 inches

Overall Height:

3.330 inches

Overall Width:

2.280 inches

Case Material:

Plastic

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.063 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

6 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

220.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1500.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Reset



Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

12.000 at 125 pct all locations and 30.000 at 125 pct all locations and 6.000 at 150 pct all locations and 20.000 at 150 pct all locations and 3.000 at 200 pct all locations and 9.000 at 200 pct all locations

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0