NSN 5925-00-689-8068



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-689-8068 **Body Style:** Single pole type **Body Length:** 6.000 inches **Body Width:** 1.375 inches **Body Height: 3.187** inches **Case Material: Plastic Unthreaded Mounting Hole Diameter:** 0.187 inches **Boss Height:** 0.188 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 unthreaded hole **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac single location and 15.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 120.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac single location and 5000.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal-magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 100.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset

Actuator Position Designation:

At pole one

NSN 5925-00-689-8068

Circuit Breaker - Page 2 of 2



Trip Delay Time In Seconds Per Rated Continuous Current:

26.000 at 200 pct single location and 80.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant

Trip Release Ambient Tempurature Rating:

25.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A030a0