

View Online at <https://aerobasegroup.com/nsn/5925-00-690-5974>

Overall Length:

1.750 inches

Overall Height:

2.570 inches

Overall Width:

0.630 inches

Case Material:

Metal

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

2.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

500.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Reset

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.150 at 200 pct single location and 0.800 at 200 pct single location and 0.050 at 300 pct single location and 0.370 at 300 pct single location and 0.010 at 400 pct single location and 0.190 at 400 pct single location

Incllosure Protection Type For Which Designed:

Hermetically sealed

Frequency In Hertz:

400.0 single location

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0